



Scale: 0.75:1

	OUTER	INNER	SEPARATOR	BALL
MATERIAL	440CS	440CS	BRASS	52100
HARDNESS	Re 55-58	Re 55-58		
RACE RUN-OUT	OUTER	INNER		
ABBRACATING	PRELUM	BULLINGEMENT		
1	N/A	QUANTITY	3/4	
		75	1/8	
RADIAL LOAD	THRUST LOAD	MOMENT LOAD		
DYNAMIC: 955 Lbs. STATIC: 1900 Lbs.	DYNAMIC: 1570 Lbs. STATIC: 4760 Lbs.	DYNAMIC: 2340 in-Lbs. STATIC: 5930 in-Lbs.		
ROSKOPF PLAY	CONTACT ANGLE	LIMITING SPEED		
0.0020	N/A	335 RPM		
0.0030				
LUBRICATION	SEAL	BEARING HEIGHT		
Mobil 28	N/A	0.98 Lbs.		

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES

Designed by ML Checked by ML

This drawing and the information contained herein are proprietary and the property of Rulbearing Corporation.

RT01-00625PAA New-Geared Thin Section Turntable Bearing

File name: RT01-00625PAA Date: November 10, 2022 REVISION: A Sheet: 1 of 1

Corporate Headquarters
15151 Putter Drive
Covington, GA 30014
(800) 431-1980
www.rulbearing.com